

VOLATILITY-ADAPTIVE DOUBLE TOP PATTERN DETECTION: A HYBRID GEOMETRIC-NEURAL NETWORK FRAMEWORK FOR ALGORITHMIC TRADING

Naimish Vadodariya and Nilesh Gambhava

Department of Computer Science and Engineering, Darshan University, India

Abstract

Technical chart patterns serve as crucial indicators for algorithmic trading systems, yet automated detection remains challenging due to pattern variability and market noise. This paper presents a novel hybrid framework that combines rule-based geometric constraints with Artificial Neural Networks (ANN) for robust Double Top (DT) pattern identification in financial time series. Our methodology employs adaptive thresholding derived from Average True Range (ATR) metrics, swing point prominence analysis, and post-breakout trend confirmation. The ANN component, trained on 16,234 historical patterns across 500 stocks, achieves pattern classification with an accuracy of 88.1% and an F1-score of 82.3%. We introduce a composite validation scoring system integrating geometric fidelity (38%), volume dynamics (27%), breakout quality (22%), and trend confirmation (13%). Experimental results on S&P 500 constituents demonstrate superior performance over baseline methods, with a precision of 83.4%, a recall of 81.2%, and an F1-score of 82.3%, along with a mean absolute error of 3.1% in measured move projections. The framework reduces false positives by 37% compared to traditional rule-based approaches while maintaining computational efficiency suitable for real-time deployment.

Keywords:

Double Top Pattern, Chart Pattern Recognition, Artificial Neural Networks, Algorithmic Trading, ATR-Based Adaptation

1. INTRODUCTION

1.1 MOTIVATION

Financial market prediction has evolved from manual chart analysis to sophisticated algorithmic systems capable of processing vast amounts of market data in real-time [1], [2]. Among classical technical analysis patterns, the Double Top (DT) represents a critical bearish reversal formation characterized by two distinct price peaks at approximately equal levels, separated by an intermediate trough [3]. While experienced traders can visually identify these patterns, automated detection systems face substantial challenges: pattern morphology varies across different timeframes and volatility regimes, noise in financial data obscures genuine formations, and strict geometric constraints often miss valid patterns while relaxed criteria generate excessive false positives [4].

The practical importance of DT patterns in portfolio management is well-documented. According to Bulkowski's statistical analysis of 5,324 DT patterns, successful formations yield average declines of 18% with 83% success rate in bear markets [1]. However, manual identification scales poorly for modern portfolio management systems monitoring hundreds of securities simultaneously. This operational constraint motivates the development of robust automated detection frameworks.

1.2 RESEARCH GAP

Existing approaches predominantly employ either pure rule-based systems with fixed thresholds [5] or machine learning models lacking domain-specific geometric validation [6]. Rule-based methods suffer from parameter sensitivity and inability to generalize across different market conditions [7]. Pure machine learning approaches, while adaptive, may detect statistically significant patterns that lack the structural properties required for reliable trading signals [4]. Furthermore, most systems neglect post-breakout validation, a critical component for confirming pattern completion and reducing premature signals [8].

1.3 CONTRIBUTIONS

This paper addresses these limitations through the following contributions:

- A hybrid detection framework integrating rule-based geometric validation with ANN-based pattern classification, combining interpretability with adaptability.
- ATR-based adaptive thresholding that dynamically adjusts detection parameters according to market volatility, improving robustness across different securities and market regimes.
- Comprehensive post-breakout confirmation mechanism requiring sustained trend direction and minimum price movement, reducing false positive rates by 43% and premature breakout signals substantially.
- Multi-faceted validation scoring system quantifying pattern quality across geometric, volumetric, and trend dimensions, enabling ranked detection suitable for portfolio-level deployment.
- Extensive empirical evaluation on 500 S&P 500 constituents over 10 years (2014–2024), demonstrating superior performance metrics and practical applicability.

2. LITERATURE REVIEW

2.1 TECHNICAL ANALYSIS FOUNDATIONS

Technical analysis, formalized by Dow [2] and systematized by Edwards and Magee [3], posits that historical price movements contain predictive information. The Double Top pattern, classified as a major reversal formation, emerges when advancing prices establish resistance at similar levels twice before reversing downward [1]. Classical identification requires: (1) prior uptrend establishing bullish context, (2) two distinct peaks within 3–5% price similarity, (3) intermediate trough separating peaks, (4) declining volume at second peak, and (5) breakout below neckline with volume surge [8].

2.2 PATTERN RECOGNITION APPROACHES

2.2.1 Rule-Based Methods:

The foundational work by Lo et al. [5] introduced computational methods for identifying chart patterns through kernel-smoothed price data. While their template-matching framework successfully automated recognition tasks, classification performance remained limited to approximately 63% for head-and-shoulders formations. Wang and Chan [4] implemented perceptually important points (PIP) segmentation for double pattern detection, reporting 69% precision but 54% recall due to overly restrictive constraints. Zapanis and Tsinaslanidis [9] applied wavelet analysis for pattern identification, achieving 66% accuracy across multiple formations [9].

2.2.2 Machine Learning Approaches:

Support Vector Machines (SVM) demonstrated promise in Leigh et al.'s work [7], achieving 73% accuracy on bull flag patterns using momentum indicators as features. While soft computing methods have been extensively catalogued for financial forecasting [6], their application to geometric pattern recognition has received less attention. Tsinaslanidis and Zapanis [10] applied convolutional neural networks (CNN) to candlestick chart images, reporting 81% accuracy but limited interpretability. Cao et al. [11] employed Long Short-Term Memory (LSTM) networks for pattern-based trading, achieving Sharpe ratios of 1.23 versus 0.87 for baseline strategies.

2.2.3 Hybrid Systems:

Dempster and Jones [12] combined genetic algorithms with technical rules, evolving optimal parameter sets for specific securities. Their approach yielded 15.3% annualized returns but required 6-month retraining periods. Hassan et al. [13] fused hidden Markov models with pattern recognition, achieving 76% directional accuracy. More recently, Sezer and Ozbayoglu [14] proposed deep learning frameworks incorporating multiple technical indicators, reporting an 82% accuracy on classification tasks. Notably, the majority of prior hybrid approaches do not incorporate adaptive geometric thresholding or post-breakout confirmation, limiting their applicability across different volatility regimes.

2.3 ADAPTIVE THRESHOLD SYSTEMS

Market volatility significantly impacts the reliability of pattern detection. Following Wilder's volatility metric [15], the Average True Range (ATR) captures the magnitude of price movement. This indicator, computed as the exponential moving average of true range values, provides a normalized measure of price variability suitable for cross-security comparison. Kaastra and Boyd [16] demonstrated neural network performance improvements when inputs include volatility-normalized features. Chen and Huang [17] applied particle swarm optimization for adaptive threshold selection in pattern trading systems, achieving an 11.2% improvement over fixed parameters.

2.4 VOLUME ANALYSIS

Our framework incorporates volume analysis as a critical validation layer, recognizing that price movements accompanied by atypical trading activity signal institutional participation rather

than retail noise. Prior empirical research [18] supports the predictive relationship between volume patterns and subsequent price behavior, motivating our integration of four volume-derived features. Granville's volume principles [19] emphasize declining volume at the second peak and surging volume at breakout. Lee and Swaminathan [20] demonstrated that momentum strategies combining price patterns with volume metrics outperform price-only approaches by 7.3% annually.

2.5 POST-BREAKOUT VALIDATION

Pattern completion requires breakout confirmation to avoid false signals. Bulkowski [1] documented that 35% of apparent breakouts fail within five bars. Nison [21] emphasized sustained movement post-breakout for reliable signals. Recent work by Marshall et al. [22] correlated breakout sustainability with liquidity metrics, finding high-volume breakouts succeed 76% versus 48% for low-volume cases.

2.6 SUMMARY OF RESEARCH GAPS

Despite extensive research, several limitations persist:

- Most systems employ fixed thresholds unsuitable for varying volatility regimes [4], [7].
- Pure ML approaches lack geometric interpretability required for trading compliance [10].
- Limited attention to post-breakout confirmation results in premature signals [1].
- Few studies provide comprehensive validation metrics beyond binary classification [6].

Our framework addresses these gaps through adaptive thresholding, hybrid architecture, rigorous post-breakout validation, and multi-dimensional scoring.

3. METHODOLOGY

3.1 SYSTEM ARCHITECTURE

The proposed framework comprises five integrated stages (Fig.1): (1) Data Preprocessing and Swing Point Detection, (2) Adaptive Threshold Computation, (3) Rule-Based Candidate Detection, (4) ANN-Based Pattern Classification, and (5) Post-Breakout Validation and Scoring.

3.2 DATA PREPROCESSING

3.2.1 Input Data Structure:

The system processes OHLCV (Open, High, Low, Close, Volume) time series data represented as:

$$D = \{(t_i, O_i, H_i, L_i, C_i, V_i) | i = 1, 2, \dots, n\} \quad (1)$$

where t_i denotes timestamp, and price/volume metrics are indexed accordingly.

3.2.2 Swing Point Detection:

We implement three complementary swing identification methods:

- **Rolling Window Method:** A swing high at index i satisfies:

$$H_i = \max(H_{i-N}, \dots, H_i, \dots, H_{i+N}) \quad (2)$$

where N represents the lookback/lookahead window (default: 20 bars).

- **ZigZag Method:** Flags reversals exceeding threshold θ :

$$\frac{C_i - C_{\text{prev}}}{C_{\text{prev}}} \geq \theta \quad (3)$$

where C_{prev} denotes the previous swing point (default $\theta = 3\%$).

- **Fractal Method:** Williams Fractals identify local extrema within symmetric windows [23].




Fig.1. Proposed hybrid framework for Double Top (DT) pattern detection. The five-stage pipeline processes raw OHLCV data (Stage 1), computes ATR-based adaptive thresholds (Stage 2), applies rule-based geometric filtering with a fallback relaxed-threshold pass (Stage 3), classifies candidates via ANN with invalid patterns discarded (Stage 4), and confirms patterns through post-breakout validation and composite scoring (Stage 5)

3.3 ADAPTIVE THRESHOLD COMPUTATION

Market volatility directly impacts pattern scale. We employ ATR-based adaptive thresholding:

3.3.1 ATR Calculation:

True Range at bar i :

$$TR_i = \max(H_i - L_i, |H_i - C_{i-1}|, |L_i - C_{i-1}|) \quad (4)$$

ATR over period p (default: 14):

$$ATR_p = \frac{1}{p} \sum_{i=n-p+1}^n TR_i \quad (5)$$

3.3.2 Adaptive Parameters:

Volatility percentage:

$$\sigma_{ATR} = \frac{ATR_p}{C_n} \quad (6)$$

Dynamic thresholds:

$$\tau_{\text{trough}} = \max(0.02, \sigma_{ATR} \cdot \alpha) \quad (7)$$

$$\tau_{\text{prominence}} = \max(0.02, \sigma_{ATR} \cdot 0.8) \quad (8)$$

$$\tau_{\text{similarity}} = \max(0.02, \sigma_{ATR} \cdot 1.5) \quad (9)$$

where $\alpha = 1.0$ is the scaling factor, and 0.02 represents minimum bounds.

3.4 RULE-BASED CANDIDATE DETECTION

3.4.1 Geometric Constraints:

For candidate triple (T_1, Tr, T_2) representing Top1, intermediate Trough, and Top2:

- **Sequence Validation:** Ensure chronological ordering with swing flags:

$$t_{T_1} < t_{Tr} < t_{T_2},$$

$$\text{swing_high}(T_1, T_2), \text{swing_low}(Tr) \quad (10)$$

- **Temporal Spacing:** Duration constraints prevent V-shaped noise:

$$d_{\min} \leq (t_{T_2} - t_{T_1}) \leq d_{\max} \quad (11)$$

where $d_{\min} = 20$ days, $d_{\max} = 90$ days.

- **Peak Similarity:** Top levels within tolerance:

$$\frac{|H_{T_1} - H_{T_2}|}{\max(H_{T_1}, H_{T_2})} \leq \tau_{\text{similarity}} \quad (12)$$

3.4.2 Strict Peak Validation Rules:

Additional constraints ensure pattern quality:

- **Maximum Top Height Difference:**

$$\frac{|H_{T_1} - H_{T_2}|}{\max(H_{T_1}, H_{T_2})} \leq \tau_{\text{strict}} = 0.02 \text{ (2\%)} \quad (13)$$

- **Local Peak Window Rule:** Top2 must be highest within $\pm w$ bars:

$$H_{T_2} = \max(H_{T_2-w}, \dots, H_{T_2}, \dots, H_{T_2+w}) \quad (14)$$

where $w = 10$ bars (local peak window).

3.4.3 Prominence Requirements:

Each peak must exhibit local prominence:

$$\text{prominence}(T_i) = \frac{H_{T_i} - \min(L_{\text{left}}, L_{\text{right}})}{H_{T_i}} \geq \tau_{\text{prominence}} \quad (15)$$

where L_{left} , L_{right} denote minimum lows in $\pm k$ bars (default $k = 5$).

- **Trough Depth:** Sufficient decline from peaks:

$$\frac{\min(H_{T_1}, H_{T_2}) - L_{Tr}}{\min(H_{T_1}, H_{T_2})} \geq \tau_{\text{trough}} \quad (16)$$

3.4.4 Minimum Move Requirements:

Enforce significant price swings between landmarks:

- **Top1 to Trough:**

$$\frac{H_{T_1} - L_{Tr}}{H_{T_1}} \geq \tau_{\text{move}} = 0.03 \text{ (3\%)} \quad (17)$$

- **Trough to Top2:**

$$\frac{H_{T_2} - L_{Tr}}{L_{Tr}} \geq \tau_{\text{move}} = 0.03 \text{ (3\%)} \quad (18)$$

3.4.5 Trend Prerequisite:

Preceding uptrend validation ensures reversal context. Over lookback period $w = 90$ bars:

$$C_{\text{start}} < H_{T_1} \cdot (1 - \tau_{\text{trend}}) \quad (19)$$

where C_{start} represents close price at $t_{T_1} - w$, and $\tau_{\text{trend}} = 0.15$ (15% advance).

3.5 BREAKOUT DETECTION

3.5.1 Neckline Definition:

The neckline level equals the intermediate trough low:

$$NL = L_{Tr} \quad (20)$$

3.5.2 Breakout Criteria:

Bearish breakout occurs when:

$$C_j \langle NL \cdot (1 - \tau_{\text{break}}), j \rangle t_{T_2} \quad (21)$$

where $\tau_{\text{break}} = 0.015$ accounts for noise tolerance.

- **Volume Confirmation:** Either condition suffices:

$$V_j > \bar{V}_{\text{pattern}} \cdot \mu_{\text{vol}} \quad (22)$$

$$\text{or } \sum_{k=j}^{j+5} 1(C_k < NL) \geq 2 \quad (23)$$

where $\bar{V}_{\text{pattern}}$ denotes average volume during pattern formation, $\mu_{\text{vol}} = 1.75$ for strict mode, and the alternative requires sustained closes below neckline.

3.6 ANN-BASED PATTERN CLASSIFICATION

3.6.1 Network Architecture:

We employ a feedforward neural network with architecture:

- Input layer: 18 features
- Hidden layer 1: 64 neurons (ReLU activation)
- Dropout: 0.3
- Hidden layer 2: 32 neurons (ReLU activation)

- Dropout: 0.2

- Output layer: 3 neurons (Softmax) for classes: {Valid DT, Invalid DT, Uncertain}

3.6.2 Feature Engineering:

The 18-dimensional feature vector $\mathbf{x}$ comprises:

- **Geometric features (6):**

$$f_1 = \frac{|H_{T_1} - H_{T_2}|}{\max(H_{T_1}, H_{T_2})} \text{ (peak similarity)} \quad (24)$$

$$f_2 = \frac{\min(H_{T_1}, H_{T_2}) - L_{Tr}}{\min(H_{T_1}, H_{T_2})} \text{ (pattern depth)} \quad (25)$$

$$f_3 = (t_{T_2} - t_{T_1}) \text{ (duration in days)} \quad (26)$$

$$f_4 = \frac{t_{Tr} - t_{T_1}}{t_{T_2} - t_{T_1}} \text{ (trough symmetry)} \quad (27)$$

$$f_5 = \text{prominence}(T_1) \quad (28)$$

$$f_6 = \text{prominence}(T_2) \quad (29)$$

- **Volume features (4):**

$$f_7 = \frac{\bar{V}_{T_1 \rightarrow Tr}}{\bar{V}_{90}} \text{ (left leg volume ratio)} \quad (30)$$

$$f_8 = \frac{\bar{V}_{Tr \rightarrow T_2}}{\bar{V}_{90}} \text{ (right leg volume ratio)} \quad (31)$$

$$f_9 = \frac{V_{\text{breakout}}}{\bar{V}_{\text{pattern}}} \text{ (breakout volume spike)} \quad (32)$$

$$f_{10} = \frac{\bar{V}_{Tr \rightarrow T_2}}{\bar{V}_{T_1 \rightarrow Tr}} \text{ (volume decline ratio)} \quad (33)$$

- **Price momentum features (4):**

$$f_{11} = \frac{H_{T_1} - C_{T_1-20}}{C_{T_1-20}} \text{ (prior trend strength)} \quad (34)$$

$$f_{12} = \frac{NL - C_{\text{breakout}+5}}{NL} \text{ (post-breakout move)} \quad (35)$$

$$f_{13} = \text{RSI}(14)|_{T_2} \text{ (relative strength index)} \quad (36)$$

$$f_{14} = \text{MACD}|_{T_2} \text{ (momentum indicator)} \quad (37)$$

- **Volatility features (2):**

$$f_{15} = \frac{ATR_{14}}{C_n} \text{ (normalized ATR)} \quad (38)$$

$$f_{16} = \frac{\sigma_{\text{price}}}{C_{\text{pattern}}} \text{ (price volatility)} \quad (39)$$

- **Market context (2):**

$$f_{17} = \frac{C_n - MA_{50}}{MA_{50}} \text{ (price vs. moving average)} \quad (40)$$

$$f_{18} = \text{avg_return}_{20} \quad (\text{recent market returns}) \quad (41)$$

3.6.3 Training Procedure:

Training dataset: 16,234 labeled patterns (8,912 valid DT, 5,127 false positives, 2,195 uncertain) extracted from 500 S&P 500 stocks (2014–2024). Loss function:

$$L = -\frac{1}{N} \sum_{i=1}^N \sum_{c=1}^3 y_{ic} \log(\hat{y}_{ic}) \quad (42)$$

where y_{ic} denotes true label and $\hat{y}_{ic}$ predicted probability for class c .

- **Optimizer:** Adam with learning rate $\eta = 0.001$, batch size 64, 100 epochs with early stopping (patience: 10 epochs).

3.7 POST-BREAKOUT VALIDATION

Critical for reducing false signals, this stage confirms sustained movement post-breakout.

3.7.1 Sustained Trend Requirement:

For bearish breakout at bar j , examine subsequent m bars (default $m = 5$):

$$\forall k \in [j+1, j+m]: C_k < C_j \quad (43)$$

3.7.2 Minimum Move Threshold:

Require minimum price progression:

$$\frac{C_j - \min(C_{j+1}, \dots, C_{j+m})}{C_j} \geq \tau_{\text{move}} \quad (44)$$

where $\tau_{\text{move}} = 0.03$ (3% minimum downward movement).

3.8 PATTERN VALIDATION AND SCORING

3.9 MULTI-DIMENSIONAL SCORING:

Detected patterns receive composite scores across four dimensions:

- **Geometric Score (S_G , weight: 38%):**

$$\begin{aligned} S_G = & 0.35 \cdot (1 - \text{norm}(f_1)) \\ & + 0.25 \cdot \text{norm}(f_2, 0.03, 0.15) \\ & + 0.20 \cdot (1 - \text{norm}(|f_4 - 0.5|)) \\ & + 0.20 \cdot \min(\text{norm}(f_5), \text{norm}(f_6)) \end{aligned} \quad (45)$$

- **Volume Score (S_V , weight: 27%):**

$$\begin{aligned} S_V = & 0.40 \cdot \text{norm}(f_9, 1.0, 3.0) \\ & + 0.30 \cdot (1 - \text{norm}(f_{10}, 0.85, 1.0)) \\ & + 0.30 \cdot \text{avg}(\text{norm}(f_7), \text{norm}(f_8)) \end{aligned} \quad (46)$$

- **Breakout Score (S_B , weight: 22%):**

$$\begin{aligned} S_B = & 0.50 \cdot \text{norm}(f_{12}, 0.03, 0.15) \\ & + 0.30 \cdot 1(\text{sustained_closes}) \end{aligned}$$

$$+ 0.20 \cdot \text{norm}(f_9, 1.5, 3.0) \quad (47)$$

- **Trend Score (S_T , weight: 13%):**

$$\begin{aligned} S_T = & 0.60 \cdot \text{norm}(f_{11}, 0.15, 0.40) \\ & + 0.40 \cdot \text{norm}(100 - f_{13}, 60, 80) \end{aligned} \quad (48)$$

- **Composite Score:**

$$S_{\text{total}} = 0.38S_G + 0.27S_V + 0.22S_B + 0.13S_T \quad (49)$$

where $\text{norm}(x, a, b)$ maps x from range $[a, b]$ to $[0, 1]$ with saturation.

3.9.1 Measured Move Projection:

Traditional measured move projects pattern height below breakout:

$$P_{\text{target}} = NL - (\min(H_{T_1}, H_{T_2}) - L_{Tr}) \quad (50)$$

4. EXPERIMENTAL SETUP

4.1 DATASET

The experimental dataset encompasses the following specifications:

- **Securities:** 500 stocks from the S&P 500 index
- **Period:** January 2014 – December 2024 (10 years)
- **Frequency:** Daily OHLCV data
- **Data Sources:** Historical data spanning 1994–2023 combined with live data from Yahoo Finance API (2023–2024)
- **Total observations:** 1,247,500 daily bars
- **Patterns detected:** 2,518 DT candidates
- **Training set:** 70% (1,763 patterns, 2014–2020)
- **Validation set:** 15% (378 patterns, 2021–2022)
- **Test set:** 15% (377 patterns, 2023–2024)

Note: The 16,234 labeled patterns used for ANN training (Section 3.6) were extracted from a broader historical dataset spanning 1994–2023, while the 2,518 DT candidates above refer specifically to the experimental evaluation window (2014–2024) used for baseline comparison.

The dataset leverages three decades of historical market data (1994–2023) to train and validate the ANN component, ensuring exposure to diverse market conditions including the dot-com bubble (2000), financial crisis (2008), and COVID-19 pandemic (2020). Live data integration through Yahoo Finance API enables real-time validation and ensures the framework's applicability to current market dynamics. This comprehensive temporal coverage spanning bull markets, bear markets, and high-volatility regimes strengthens the model's generalization capability across varied economic cycles.

4.2 BASELINE METHODS

1. **Fixed-Rule Baseline:** Traditional geometric constraints without adaptive thresholds [4].
2. **SVM Classifier:** RBF kernel with same feature set [7].

3. **Random Forest:** 100 trees, max depth 10 [6].
4. **LSTM Network:** 2-layer LSTM (64, 32 units) for sequence classification [11].

4.3 EVALUATION METRICS

4.3.1 Classification Metrics:

$$\text{Precision} = \frac{TP}{TP + FP} \quad (51)$$

$$\text{Recall} = \frac{TP}{TP + FN} \quad (52)$$

$$\text{F1-Score} = \frac{2 \cdot \text{Precision} \cdot \text{Recall}}{\text{Precision} + \text{Recall}} \quad (53)$$

$$\text{Accuracy} = \frac{TP + TN}{TP + TN + FP + FN} \quad (54)$$

4.3.2 Trading Performance:

$$\text{Success Rate} = \frac{\text{\#profitable patterns}}{\text{\#total patterns}} \quad (55)$$

$$\text{Avg. Return} = \frac{1}{n} \sum_{i=1}^n \frac{P_{\text{entry},i} - P_{\text{exit},i}}{P_{\text{entry},i}} \quad (56)$$

$$\text{Sharpe Ratio} = \frac{\bar{R} - R_f}{\sigma_R} \quad (57)$$

4.3.3 Pattern Quality:

$$\text{MAE}_{\text{target}} = \frac{1}{n} \sum_{i=1}^n |P_{\text{actual},i} - P_{\text{projected},i}| \quad (58)$$

4.4 IMPLEMENTATION

All experiments were conducted using Python 3.9 with PyTorch 1.12 on an NVIDIA RTX 3090 GPU (24 GB VRAM) and Intel Core i9-12900K CPU. Average processing time was 0.13 s per stock on daily data spanning two years.

5. RESULTS AND ANALYSIS

5.1 CLASSIFICATION PERFORMANCE

The Table.1 presents comprehensive classification metrics across all methods on the test set.

Table.1. Classification Performance Comparison

Method	Precision	Recall	F1	Accuracy
Fixed-Rule	68.7%	72.4%	70.5%	74.6%
SVM	75.8%	77.3%	76.5%	79.8%
Random Forest	79.6%	78.4%	79.0%	82.7%
LSTM	81.9%	80.1%	81.0%	85.2%
Proposed	83.4%	81.2%	82.3%	88.1%

Our hybrid framework achieves 83.4% precision, outperforming the second-best LSTM by 1.5 percentage points. The 88.1% accuracy represents a 2.9% improvement over LSTM

and a 13.5% improvement over the fixed-rule baseline. Statistical significance of the accuracy improvement over all baselines was confirmed via McNemar’s test ($p < 0.01$).

5.2 ABLATION STUDY

The Table.2 demonstrates the contribution of each component.

Table.2. Ablation Study Results

Configuration	Precision	Recall	F1
Full model	83.4%	81.2%	82.3%
- Adaptive thresholds	78.6%	79.4%	79.0%
- ANN classifier	77.2%	81.6%	79.3%
- Post-breakout val.	77.8%	83.7%	80.6%
- Strict peak rules	80.1%	79.8%	79.9%
- Volume features	80.3%	78.9%	79.6%
Rules only	68.7%	72.4%	70.5%
ANN only	79.8%	77.6%	78.7%

Removing adaptive thresholds reduces F1-score by 3.3%, highlighting volatility adaptation’s importance. Post-breakout validation critically reduces false positives, as evidenced by precision drop from 83.4% to 77.8% when omitted. The strict peak rules (MAX_TOP_HEIGHT_DIFF, LOCAL_PEAK_WINDOW) contribute 2.4% F1 improvement, demonstrating their effectiveness in filtering noise. The ANN component contributes 3.6% F1 improvement over pure rules, while rules provide 3.6% improvement over pure ANN, validating the hybrid approach.

5.3 TRADING PERFORMANCE

We simulated short-selling strategies entering at breakout and exiting at measured move target or 30-day timeout. Table 3 summarizes results.

Table.3. Simulated Trading Performance (Test Period)

Method	Success	Avg Return	Sharpe	Max DD
Fixed-Rule	70.2%	5.8%	0.91	−16.7%
SVM	73.8%	7.3%	1.18	−14.3%
Random Forest	76.1%	8.1%	1.31	−12.8%
LSTM	78.4%	8.9%	1.43	−11.4%
Proposed	81.2%	10.2%	1.58	−9.8%
Buy & Hold	64.2%	7.3%	0.94	−22.6%

Our framework achieves an 81.2% success rate with 10.2% average return per short trade, representing a 4.4 percentage point improvement over the fixed-rule baseline (5.8%) in absolute return terms. The Sharpe ratio of 1.58 indicates superior risk-adjusted returns, while the maximum drawdown of −9.8% demonstrates enhanced risk control. Statistical testing via bootstrap resampling (10,000 iterations) confirms significance ($p < 0.001$) for return differences versus all baselines.

5.4 PATTERN QUALITY METRICS

The Table.4 evaluates detected pattern quality across multiple dimensions.

Table.4. Pattern Quality Assessment

Metric	Fixed	LSTM	Proposed	Δ%
Avg Score	0.638	0.746	0.794	+6.4%
Geometric	0.695	0.771	0.818	+6.1%
Volume	0.607	0.728	0.773	+6.2%
Breakout	0.628	0.742	0.796	+7.3%
Trend	0.672	0.743	0.789	+6.2%
MAE Target	4.6%	3.5%	3.1%	−11.4%

The proposed method achieves average composite score of 0.794, with particular strength in breakout quality (0.796). Mean absolute error in measured move projections decreases to 3.1%, representing 33% improvement over fixed-rule baseline and 11.4% improvement over LSTM.

5.5 ADAPTIVE THRESHOLD IMPACT

The Table.5 illustrates ATR-based threshold adaptation across different volatility regimes.

Table.5. Performance Across Volatility Regimes

Regime	Fixed F1	Adaptive F1	Gain
Low Vol ($\sigma < 0.015$)	73.6%	79.4%	+5.8%
Medium Vol	71.2%	82.7%	+11.5%
High Vol ($\sigma > 0.035$)	66.8%	84.1%	+17.3%

Adaptive thresholding provides substantial benefits in high-volatility environments (+17.3% F1 improvement), where fixed thresholds generate excessive false positives. Even in low-volatility regimes, adaptation yields 5.8% F1 gain, validating the approach’s robustness.

5.6 POST-BREAKOUT VALIDATION ANALYSIS

The Table.6 quantifies post-breakout confirmation’s impact on signal reliability.

Table.6. Post-Breakout Validation Impact

Configuration	Patterns	Success Rate	FP Rate
No validation	438	68.7%	29.8%
Volume only	394	74.1%	23.4%
Sustained trend	367	77.9%	18.2%
Both criteria	351	81.2%	17.6%

Combined post-breakout validation (volume spike + sustained trend) reduces false positive rate by 43% compared to no validation (from 29.8% to 17.6%), while improving success rate by 12.5 percentage points. Though pattern count decreases by 20%, signal quality substantially improves.

5.7 STRICT PEAK RULES EFFECTIVENESS

The Table.7 evaluates the impact of strict geometric constraints on Double Top detection.

Table.7. Strict Peak Rules Impact

Configuration	Patterns	Precision	Success Rate
Basic similarity only	487	74.6%	72.1%
+ Max height diff (2%)	421	78.9%	76.3%
+ Local peak window	389	81.2%	78.8%
+ Min move (3%)	351	83.4%	81.2%

The strict peak validation rules progressively filter weak patterns: enforcing 2% maximum top height difference improves precision by 4.3%, the local peak window constraint adds 2.3%, and minimum move requirements contribute 2.2%. These cumulative improvements validate the multi-layered validation strategy.

5.8 ANN FEATURE IMPORTANCE

Feature importance analysis via permutation testing reveals key predictive factors (Table 8).

Table.8. Top 10 Feature Importance Rankings

Feature	Importance	Category
f_9 (Breakout vol spike)	0.148	Volume
f_{12} (Post-breakout move)	0.132	Momentum
f_2 (Pattern depth)	0.121	Geometric
f_1 (Peak similarity)	0.114	Geometric
f_{10} (Volume decline)	0.096	Volume
f_5 (Top1 prominence)	0.088	Geometric
f_{11} (Prior trend)	0.082	Momentum
f_4 (Trough symmetry)	0.074	Geometric
f_{15} (Normalized ATR)	0.069	Volatility
f_{13} (RSI)	0.065	Momentum

Breakout volume spike (f_9) emerges as the most predictive feature (14.8% importance), followed by post-breakout movement (f_{12} , 13.2%) and pattern depth (f_2 , 12.1%). Volume decline ratio (f_{10}) at 9.6% importance confirms that lower volume at the second peak correlates with pattern validity, consistent with exhaustion principles in technical analysis [19].

5.9 COMPUTATIONAL EFFICIENCY

The Table.9 compares computational requirements across methods. Despite incorporating neural network classification, our framework processes each stock (500 days data) in 0.13s, 71% faster than LSTM while maintaining modest memory footprint (305 MB). The hybrid architecture balances computational efficiency with prediction accuracy, enabling real-time deployment for portfolio-level monitoring.

Table.9. Computational Performance

Method	Time/Stock	Memory	Scalability
Fixed-Rule	0.07s	118 MB	Excellent
SVM	0.29s	274 MB	Good
Random Forest	0.18s	398 MB	Good
LSTM	0.45s	1.7 GB	Moderate
Proposed	0.13s	305 MB	Excellent

5.10 CROSS-VALIDATION RESULTS

Five-fold cross-validation ensures generalization across different market periods.

Table.10. 5-Fold Cross-Validation Results

Fold	Precision	Recall	F1	Accuracy
Fold 1	84.1%	80.3%	82.2%	87.6%
Fold 2	82.9%	81.8%	82.3%	88.2%
Fold 3	83.7%	80.7%	82.2%	87.9%
Fold 4	82.6%	82.4%	82.5%	88.4%
Fold 5	83.9%	80.9%	82.4%	88.3%
Mean	83.4%	81.2%	82.3%	88.1%
Std Dev	0.61%	0.89%	0.12%	0.31%

Low standard deviation across folds (F1 std: 0.12%) demonstrates stable performance. Mean metrics closely match test set results, confirming model generalization without overfitting.

5.11 ERROR ANALYSIS

Analysis of 78 false positives and 74 false negatives (a representative subset of 34 FPs and 31 FNs manually reviewed in detail) reveals systematic error patterns:

5.11.1 False Positives (34 analyzed):

- 41.2% – Weak preceding uptrend (marginal qualification)
- 26.5% – Neckline breakout failed to sustain (reversed within 10 bars)
- 20.6% – Third top formed (actually triple top pattern)
- 11.7% – Low volume breakout with insufficient confirmation

5.11.2 False Negatives (31 analyzed):

- 45.2% – Irregular trough position (asymmetric formation)
- 25.8% – Peak similarity at boundary (3.2–3.6% difference)
- 19.3% – Extended duration beyond 90-day limit
- 9.7% – Insufficient preceding trend magnitude

These insights suggest future improvements: relaxing duration constraints for trending markets, implementing triple-top detection, and enhancing asymmetric pattern tolerance.

5.12 COMPARISON ACROSS MARKET CONDITIONS

The Table.11 evaluates framework performance during different market regimes.

Table.11. Performance by Market Regime

Market Regime	Patterns	F1	Success	Avg Return
Bull Market (VIX < 15)	127	79.8%	77.2%	8.4%
Normal (VIX 15–25)	186	83.6%	82.8%	10.9%
Volatile (VIX 25–35)	29	81.4%	84.1%	12.6%
Crisis (VIX > 35)	9	74.3%	88.9%	15.3%

Interestingly, Double Top patterns perform best during crisis periods (88.9% success rate, 15.3% average return), as bearish reversals are more pronounced during market panic. Performance remains robust across all regimes, with F1-scores above 74% even in challenging conditions.

5.13 FALLBACK PASS ANALYSIS

The detection algorithm implements a fallback pass with relaxed thresholds when initial pass finds no patterns. The Table.12 quantifies its contribution.

Table.12. Fallback Pass Contribution

Source	Patterns	Precision	Success Rate
First pass (strict)	289	86.2%	83.7%
Fallback pass	62	73.4%	72.6%
Combined	351	83.4%	81.2%

The fallback pass recovers 17.7% additional patterns (62 out of 351 total) with acceptable quality (73.4% precision). While these patterns score lower than strict-pass detections, they still provide viable trading signals, demonstrating the value of adaptive multi-pass detection.

6. DISCUSSION

6.1 ADVANTAGES OF HYBRID ARCHITECTURE

The proposed hybrid framework synergistically combines rule-based geometric validation with machine learning adaptability. Rule-based components ensure detected patterns maintain structural properties required for classical technical analysis, providing interpretability crucial for trading compliance and risk management. The ANN classifier adds contextual learning, capturing subtle interactions between features that fixed rules cannot encode. This architecture outperforms pure approaches: rules-only systems lack adaptability (68.7% precision vs. 83.4%), while ANN-only methods miss geometric constraints (79.8% precision vs. 83.4%).

6.2 ATR-BASED ADAPTATION EFFECTIVENESS

Adaptive thresholding addresses a fundamental challenge: pattern scale varies with volatility. During high-volatility periods (March 2020 COVID crash, September 2022 inflation peak), fixed thresholds generated 2.6× more false positives than adaptive methods. Conversely, in low-volatility regimes (2017, early 2024), fixed thresholds missed 21% of valid patterns by requiring excessive similarity. ATR-based scaling dynamically adjusts to current market conditions, improving F1-score by 11.5% in medium-volatility and 17.3% in high-volatility environments.

6.3 STRICT PEAK RULES NECESSITY

The additional strict validation rules (MAX_TOP_HEIGHT_DIFF, LOCAL_PEAK_WINDOW, MIN_MOVE_PCT) represent key innovations for Double Top detection. The 2% maximum height difference ensures genuine peak similarity beyond general tolerance thresholds. The local peak window requirement (Top2 must be highest within ±10 bars) filters cases where the second “peak” is merely a minor retracement within a larger uptrend. The 3% minimum move constraints eliminate micro-patterns that lack sufficient magnitude for profitable trading. Together, these rules reduce false positives by 28% while maintaining 92% recall of genuine patterns.

6.4 POST-BREAKOUT VALIDATION NECESSITY

Classical technical analysis emphasizes follow-through after breakout [1], yet many automated systems neglect this principle. Our results quantify this oversight’s cost: without post-breakout validation, false positive rate reaches 29.8% versus 17.6% with validation a 43% reduction. The sustained trend requirement (all closes beyond breakout level for 5 bars + 3% minimum move) effectively filters premature breakouts that reverse quickly. While this reduces pattern count by 20%, the success rate improvement (+12.5%) substantially enhances trading viability.

6.5 VOLUME DYNAMICS CRITICAL ROLE

Volume feature importance analysis confirms Granville’s exhaustion principles [19]: breakout volume spike (f_9) ranks as the most predictive feature (14.8% importance), and volume decline ratio (f_{10}) ranks fifth (9.6%). Patterns exhibiting proper volume characteristics (declining at second peak, surging at breakout) succeed at 85.3% rate versus 71.2% for volume-anomalous patterns. This 14.1 percentage point difference validates volume analysis integration in automated detection systems. Declining volume at Top2 indicates weakening buying pressure, confirming bearish reversal momentum.

6.6 MEASURED MOVE PROJECTION ACCURACY

The framework achieves 3.1% mean absolute error in measured move target projections, enabling quantitative price target estimation. 69.4% of successful patterns reached 90–110% of projected target, while 84.3% reached at least 70%. This projection accuracy supports practical trade planning: short entry at breakout, initial target at measured move, stop-loss above Top2. Risk-reward ratios average 3.4:1, favorable for systematic short-selling strategies.

6.7 MARKET REGIME INSIGHTS

The superior performance during crisis periods (88.9% success rate, 15.3% average return) reveals important characteristics: Double Tops form more reliably when markets transition from greed to fear, as resistance levels hold more firmly during distribution phases. Normal market conditions (VIX 15–25) provide the optimal balance of pattern frequency (186 patterns) and quality (82.8% success rate). Bull markets generate fewer patterns (127) but still maintain adequate success rates (77.2%), suggesting the framework appropriately identifies

genuine reversals even in predominantly uptrending environments.

6.8 LIMITATIONS AND CHALLENGES

Despite strong performance, several limitations warrant acknowledgment:

- **Data Quality Dependency:** The system requires clean OHLCV data with accurate volume reporting. Low-liquidity securities with sparse volume may generate unreliable signals.
- **Short-Selling Constraints:** Practical implementation requires securities that are shortable with reasonable borrowing costs. During market squeezes, short interest and borrowing fees can make trading detected patterns economically unfeasible.
- **Market Regime Sensitivity:** Performance degrades during extreme momentum trends (strong bull runs) when reversal patterns break down more frequently. Extended bull market periods exhibit 8–11% lower success rates.
- **Lookback Bias:** Post-breakout validation introduces 5-bar delay (approximately 1 week), during which 7–10% of potential profit may be missed. This represents a tradeoff between signal reliability and timeliness.
- **Parameter Sensitivity:** While adaptive thresholds reduce sensitivity, parameters like d_{min} , d_{max} , and τ_{move} still require empirical tuning. Suboptimal values degrade performance by 5–8%.
- **Pattern Overlap:** When multiple patterns overlap temporally (e.g., larger DT containing smaller DT), the system may detect both, requiring deduplication logic. Currently, we retain the highest-scoring pattern per timeframe.
- **Asymmetric Formations:** The framework struggles with asymmetric Double Tops where the trough is significantly off-center (19.3% of false negatives), suggesting need for relaxed symmetry constraints.

6.9 COMPARISON WITH PRIOR LITERATURE

The Table.13 contextualizes our results within the existing literature on automated chart pattern recognition.

Table.13. Comparison with Prior Art

Study	Method	Accuracy	Pattern
Lo et al. [5]	Kernel Reg.	63%	H&S
Leigh et al. [7]	SVM	73%	Bull Flag
Wang & Chan [4]	PIP	69%	Double
Zapranis [9]	Wavelet	66%	Multiple
Tsinaslanidis [10]	CNN	81%	Multiple
Cao et al. [11]	LSTM	78%	Trend
This work	Hybrid ANN	88.1%	Double Top

Our 88.1% accuracy surpasses the previous best result (Tsinaslanidis CNN: 81%) by 7.1 percentage points. For the specific Double Top pattern category, our framework outperforms Wang & Chan’s PIP method by 19.1% in absolute accuracy. The

hybrid architecture, adaptive thresholding, and strict geometric validation collectively contribute to this performance gain.

6.9 PRACTICAL CONSIDERATIONS DEPLOYMENT

For real-world trading system integration:

- **Real-time Processing:** At 0.13s per stock, the system monitors 500 securities in 65 seconds, suitable for end-of-day analysis. Intraday deployment requires optimization (vectorization, GPU acceleration) for sub-second latency.
- **Risk Management:** Detected patterns should incorporate position sizing based on composite score. High-scoring patterns (> 0.75) might receive $1.5\times$ standard position, while lower scores (< 0.65) receive $0.5\times$ or are filtered entirely.
- **Short-Selling Infrastructure:** Implementation requires integration with securities lending systems to verify shortability and assess borrowing costs before executing trades.
- **Multi-Timeframe Analysis:** Patterns detected across multiple timeframes (daily, weekly) provide stronger signals. Weekly Double Tops confirmed by daily patterns show 89.3% success rate versus 81.2% for daily-only signals.
- **Integration with Other Indicators:** DT patterns perform best when confirmed by momentum indicators showing bearish divergence. RSI below 70 at Top2 (feature f_{13}) correlates with 6.5% higher success rates.
- **Market Context Filtering:** During confirmed bull markets (S&P 500 above 200-day MA with positive slope), reducing position sizing by 30–40% accounts for reversal pattern lower reliability in strong uptrends.

7. CONCLUSION AND FUTURE WORK

7.1 SUMMARY OF CONTRIBUTIONS

This research presents a novel hybrid framework for automated Double Top pattern detection, achieving state-of-the-art performance through:

- **Hybrid Architecture:** Synergistic integration of rule-based geometric constraints with ANN-based classification, balancing interpretability and adaptability to achieve 88.1% accuracy and 83.4% precision.
- **ATR-Based Adaptation:** Dynamic threshold adjustment based on market volatility, improving F1-score by 3.3% overall and 17.3% in high-volatility regimes versus fixed thresholds.
- **Strict Peak Validation Rules:** Novel constraints including maximum top height difference (2%), local peak window requirement (± 10 bars), and minimum move thresholds (3%), reducing false positives by 28% while maintaining 92% recall.
- **Rigorous Post-Breakout Validation:** Sustained trend confirmation reducing false positive rate by 43% (from 29.8% to 17.6%), substantially improving signal reliability for practical trading.

- **Multi-Dimensional Scoring:** Composite quality assessment across geometric, volumetric, breakout, and trend dimensions, enabling pattern ranking and risk-adjusted position sizing.

- **Empirical Validation:** Comprehensive evaluation on 10 years of S&P 500 data (2,518 patterns) demonstrating 81.2% trading success rate, 10.2% average return per short trade, and 1.58 Sharpe ratio.

7.2 IMPLICATIONS FOR ALGORITHMIC TRADING

The framework provides reliable pattern detection suitable for systematic short-selling strategies. The 3.4:1 average risk-reward ratio and 1.58 Sharpe ratio suggest favorable risk-adjusted returns. Computational efficiency (0.13s per stock) enables portfolio-level deployment, while composite scoring supports prioritized signal selection under capital constraints. Superior performance during crisis periods (88.9% success rate) positions the system as a valuable component of market-neutral or bear-market hedge strategies.

7.3 FUTURE RESEARCH DIRECTIONS

Several promising extensions warrant investigation:

- **Multi-Pattern Integration:** Combining DT detection with complementary patterns (Head and Shoulders, Descending Triangle) could improve reversal identification. Ensemble voting across multiple bearish reversal patterns may enhance reliability.
- **Deep Learning Enhancements:** Transformer architectures with attention mechanisms could better capture temporal dependencies in price series. Graph Neural Networks (GNN) might model inter-security relationships for sector-wide pattern correlation analysis.
- **Reinforcement Learning Optimization:** RL agents could learn optimal entry/exit timing given detected patterns, adaptively managing short positions based on post-breakout price action rather than fixed measured move targets.
- **Market Microstructure Integration:** Incorporating order flow data (bid-ask spreads, order book depth, short interest) could enhance breakout quality assessment, particularly for distinguishing genuine institutional distribution from retail noise.
- **Sentiment Analysis Fusion:** Integrating news sentiment and social media signals with technical patterns may improve success rate prediction, as fundamental bearish catalysts often drive pattern completion.
- **Adaptive Parameter Tuning:** Meta-learning approaches could automatically optimize detection parameters per security based on historical pattern performance, accounting for stock-specific characteristics and volatility profiles.
- **Uncertainty Quantification:** Bayesian neural networks or ensemble methods could provide confidence intervals for pattern classifications, enabling more nuanced risk assessment and position sizing.
- **Asymmetric Pattern Handling:** Developing specialized rules or attention mechanisms for asymmetric formations

could recover the 19.3% of false negatives stemming from off-center troughs.

- **Extended Pattern Library:** Expanding to detect all major technical patterns (Head & Shoulders, Triangles, Flags, Wedges) would create comprehensive pattern recognition infrastructure for algorithmic trading systems.
- **Short-Selling Cost Integration:** Incorporating securities lending data to estimate borrowing costs and availability, filtering patterns to only those with economically viable short-selling opportunities.

ACKNOWLEDGEMENT

This work utilized historical market data (1994–2023), real-time data from the Yahoo Finance API (2023–2024), and supplementary indicators from the Alpha Vantage API. The authors acknowledge the value of publicly accessible financial data in advancing research on algorithmic trading and technical analysis.

REFERENCES

- [1] T.N. Bulkowski, “*Encyclopedia of Chart Patterns*”, 2nd Edition, Wiley, 2005.
- [2] J.J. Murphy, “*Technical Analysis of the Financial Markets*”, New York Institute of Finance, 1999.
- [3] R.D. Edwards, J. Magee and W.H.C. Bassetti, “*Technical Analysis of Stock Trends*”, CRC Press, 2018.
- [4] J. Wang and S. Chan, “Stock Market Trading Rule Discovery using Pattern Recognition and Technical Analysis”, *Expert Systems with Applications*, Vol. 39, No. 8, pp. 6818-6825, 2012.
- [5] A.W. Lo, H. Mamaysky and J. Wang, “Foundations of Technical Analysis: Computational Algorithms, Statistical Inference, and Empirical Implementation”, *Journal of Finance*, Vol. 55, No. 4, pp. 1705-1765, 2000.
- [6] G.S. Atsalakis and K.P. Valavanis, “Surveying Stock Market Forecasting Techniques - Part II: Soft Computing Methods”, *Expert Systems with Applications*, Vol. 36, No. 3, pp. 5932-5941, 2009.
- [7] W. Leigh, N. Modani, R. Purvis and T. Roberts, “Stock Market Trading Rule Discovery using Technical Charting Heuristics”, *Expert Systems with Applications*, Vol. 34, No. 2, pp. 1232-1247, 2008.
- [8] C.D. Kirkpatrick and J.R. Dahlquist, “*Technical Analysis: The Complete Resource for Financial Market Technicians*”, 2nd Edition, FT Press, 2010.
- [9] A. Zapranis and A. Tsinaslanidis, “A Comprehensive Database of Stock Return Chart Patterns: Construction and Performance Evaluation”, *Proceedings of World Congress on Engineering*, pp. 892-897, 2012.
- [10] P.E. Tsinaslanidis and A.D. Zapranis, “Technical Analysis for Algorithmic Pattern Recognition”, *Proceedings of IEEE Conference on Computational Intelligence for Financial Engineering*, pp. 1-8, 2016.
- [11] J. Cao, Z. Li and J. Li, “Financial Time Series Forecasting Model based on CEEMDAN and LSTM”, *Physica A: Statistical Mechanics and its Applications*, Vol. 519, pp. 127-139, 2019.
- [12] M.A. Dempster and C.M. Jones, “A Real-Time Adaptive Trading System using Genetic Programming”, *Quantitative Finance*, Vol. 1, No. 4, pp. 397-413, 2001.
- [13] M.R. Hassan, B. Nath and M. Kirley, “A Fusion Model of HMM, ANN and GA for Stock Market Forecasting”, *Expert Systems with Applications*, Vol. 33, No. 1, pp. 171-180, 2007.
- [14] O.B. Sezer and A.M. Ozbayoglu, “Algorithmic Financial Trading with Deep Convolutional Neural Networks: Time Series to Image Conversion Approach”, *Applied Soft Computing*, Vol. 70, pp. 525-538, 2018.
- [15] J.W. Wilder, “*New Concepts in Technical Trading Systems*”, Trend Research, 1978.
- [16] I. Kaastra and M. Boyd, “Designing a Neural Network for Forecasting Financial and Economic Time Series”, *Neurocomputing*, Vol. 10, No. 3, pp. 215-236, 1996.
- [17] Y. Chen and Y. Huang, “An Adaptive Hybrid Learning Paradigm Integrating CEEMD, ARIMA and SBL for Crude Oil Price Forecasting”, *Energies*, Vol. 12, No. 7, pp. 1239-1253, 2019.
- [18] L. Blume, D. Easley and M. O’Hara, “Market Statistics and Technical Analysis: The Role of Volume”, *Journal of Finance*, Vol. 49, No. 1, pp. 153-181, 1994.
- [19] J.E. Granville, “*Granville’s New Strategy of Daily Stock Market Timing for Maximum Profit*”, Prentice Hall, 1976.
- [20] C.M.C. Lee and B. Swaminathan, “Price Momentum and Trading Volume”, *Journal of Finance*, Vol. 55, No. 5, pp. 2017-2069, 2000.
- [21] S. Nison, “*Japanese Candlestick Charting Techniques*”, 2nd Edition, Prentice Hall, 2001.
- [22] B.R. Marshall, N.H. Nguyen and N. Visaltanachoti, “Liquidity Commonality in Commodities”, *Journal of Banking and Finance*, Vol. 37, No. 1, pp. 11-20, 2008.
- [23] B.M. Williams, “*Trading Chaos: Maximize Profits with Proven Technical Techniques*”, 2nd Edition, Wiley, 1999.